



SP312/ 316EZ SLIMLINE FIRE ESCAPE/EASY CLEAN FRICTION STAY

- Full opening to 90° Providing clear egress in excess of 500mm on a 600mm wide vent, enables the window to meet Part B regulations
- Designed to accommodate staygaards that increase the security performance to BS7950
- By utilising high quality plastic components the new release mechanism provides greater corrosion resistance to BS7479
- User friendly push button operation enables window to slide smoothly along the track to the easy clean position providing access from inside the building.
- New unique patent applied for moulded component guarantees uninterrupted operation giving a safer, more efficient performance
- To reset simply close the window and then re-open to go back to the egress position and close
- When fitting the SP312 /316 please observe. BS8213 Part 1: 1991 Code of practice for safety in use and during cleaning of windows.

RECOMMENDED MAXIMUM WINDOW WEIGHTS & SIZES

APPLICATION	PRODUCT	SIZE INS	SIZE MM	WINDOW SIZE APPROX WIDTH MM	WINDOW SIZE APPROX HEIGHT MM	WINDOW WEIGHT APPROX KG	STACK HEIGHT MM	OPENING ANGLE
SIDE HUNG	SP316EZ (HANDED)	16	413	600	1200	21	13 & 17	89°
SIDE HUNG	SP312EZ (HANDED)	12	311	600	1200	18 or 21 with Riser	13 & 17	85°

Available in Ferretic steel (normal applications) and Austenitic steel (coastal / high humidity areas)

IT IS THE RESPONSIBILITY OF THE WINDOW MANUFACTURER TO ENSURE THAT THE FINISHED WINDOW MEET ANY REQUIRED SAFETY AND PERFORMANCE SPECIFICATIONS