



HD16 EGRESS HEAVY DUTY FRICTION STAY

Heavy-Duty Egress friction stay for enhanced performance with timber, Upvc and large section aluminium.

- Full opening to 90° Providing clear egress in excess of 500mm on a 600 wide vent (Depending on Profile)
- Easy to fit with adjustable friction mechanism.
- Smooth and balanced operation for life – windows open and close with ease.
- Effective weather sealing and draught proofing fully concealed once fitted.
- Corrosion resistance meets the requirements of BS 7412: 1991.
- Manufactured from high-grade Austenitic stainless steel for maximum longevity. Even in the most corrosive environments.
- Composite steel /plastic slider for strength, durability and smooth operation.
- The Heavy Duty range has been proven to a lifetime 50,000 cycles.
- The Heavy Duty friction stays conform to all leading international window performance standards in the UK (BS6375 Part 2 1987), North America (AAMA 904.1), France (NFP-20-302) and Singapore (SS 212 1998).
- On any windows over 32Kg we recommend that you fit our Heavy Duty Friction Arms (HD102)

RECOMMENDED MAXIMUM WINDOW WEIGHTS & SIZES

PRODUCT	TOP/SIDE HUNG	SIZE INS	SIZE MM	WINDOW SIZE APPROX WIDTH MM	WINDOW SIZE APPROX HEIGHT MM	WINDOW WEIGHT APPROX KG	MAXIMUM OPENING ANGLE
HD16E	SIDE	16	412	762	1619	42Kg	90°

IT IS THE RESPONSIBILITY OF THE WINDOW MANUFACTURER TO ENSURE THAT THE FINISHED WINDOW MEET ANY REQUIRED SAFETY AND PERFORMANCE SPECIFICATIONS