



FRICITION STAYS

- Available in 8, 10, 12", 16", 20" and 24" top hung and 12" and 16" for side hung applications.
- Manufactured in the United Kingdom using high-grade Austenitic and Ferretic stainless steel.
- These stays have been proven to a lifetime 30,000 cycle guarantee
- Conforms to the requirements of BS6375 Part 2 1987

RECOMMENDED MAXIMUM WINDOW WEIGHTS & SIZES

PRODUCT	SIZE INS	SIZE MM	APPLICATION	WINDOW SIZE APPROX WIDTH MM	WINDOW SIZE APPROX HEIGHT MM	WINDOW WEIGHT APPROX	STACK HEIGHT MM	OPENING ANGLE
FS100 8"	8	210	TOP HUNG	1200	300	10	13/14 & 16/17	62
FS100 10"	10	260	TOP HUNG	1200	450	16	13/14 & 16/17	56
FS100 12"	12	311	TOP HUNG	1200	600	21	13/14 & 16/17	64
FS100 16"	16	406	TOP HUNG	1200	750	22	13/14 & 16/17	51
FS100 20"	20	511	TOP HUNG	1200	900	24	13/14 & 16/17	42
FS100 24"	24	615	TOP HUNG	1200	1200	32	13/14 & 16/17	38
FS90 10"	10	311	TOP HUNG	1200	450	16	13/14 & 16/17	90
FS90 16"	16	406	TOP HUNG	1200	750	22	13/14 & 16/17	83
SH101	12	311	SIDE HUNG	600	1200	18	13/14 & 16/17	64
SH101-16"	16	406	SIDE HUNG	700	1300	24	13/14 & 16/17	51

IT IS THE RESPONSIBILITY OF THE WINDOW MANUFACTURER TO ENSURE THAT THE FINISHED WINDOW MEET ANY REQUIRED SAFETY AND PERFORMANCE SPECIFICATIONS