



SINIDEX SLIMLINE HANDED STAY

Cotswold's Sinidex Slimline stays offer improved security and weather sealing through the use of a Nylon reduced friction end cap. These stays have been designed to offer smooth closure and higher performance for window applications of all sizes.

- Available in 8, 10, 12", 16", 20" and 24" top hung and 12" for side hung applications.
- 15mm Channel width to suit reduced width Euro Grooves
- Manufactured in the United Kingdom using high-grade Austenitic and Ferritic stainless steel.
- The stays have been proven to a lifetime 30,000 cycle guarantee

RECOMMENDED MAXIMUM WINDOW WEIGHTS & SIZES

PRODUCT	SIZE INS	SIZE MM	APPLICATION	WINDOW SIZE APPROX WIDTH MM	WINDOW SIZE APPROX HEIGHT MM	WINDOW WEIGHT APPROX	STACK HEIGHT MM	OPENING ANGLE
HS100 8"	8	210	TOP HUNG	1200	300	10	13/14 & 16/17	62
HS100 10"	10	260	TOP HUNG	1200	450	16	13/14 & 16/17	56
HS100 12"	12	311	TOP HUNG	1200	600	21	13/14 & 16/17	64
HS100 16"	16	406	TOP HUNG	1200	750	22	13/14 & 16/17	51
HS100 20"	20	511	TOP HUNG	1200	900	24	13/14 & 16/17	42
HS100 24"	24	615	TOP HUNG	1200	1200	32	13/14 & 16/17	38
HS201	12	311	TOP/SIDE HUNG	650	1250	20	13/14 & 16/17	60

IT IS THE RESPONSIBILITY OF THE WINDOW MANUFACTURER TO ENSURE THAT THE FINISHED WINDOW MEET ANY REQUIRED SAFETY AND PERFORMANCE SPECIFICATIONS