



SECURITY STAY

Cotswold Security stays are strong, smooth operating, and provide effective protection from window break-ins. Proven in tests to resist human intervention for three minutes and will withstand in excess of 3,500 Newton's of applied force. The strengthened end cap and heavy-duty vent arm will ensure that the stays themselves will not give way, even when leverage is applied.

The unique design of the vent arm and end cap ensures enhanced weather seal, positive closure and smooth interference free operation of the stays, due to the location of the metal against the plastic cap cover.

- Available in 8, 10, 12", 16", 20" and 24" top hung and 12" and 16" for side hung applications.
- Manufactured in the United Kingdom using high-grade Austenitic and Ferretic stainless steel.
- The stays have been proven to a lifetime 30,000 cycle guarantee
- Conforms to the requirements of BS6375 Part 2 1987

RECOMMENDED MAXIMUM WINDOW WEIGHTS & SIZES

PRODUCT	SIZE INS	SIZE MM	APPLICATION	WINDOW SIZE APPROX WIDTH MM	WINDOW SIZE APPROX HEIGHT MM	WINDOW WEIGHT APPROX	STACK HEIGHT MM	OPENING ANGLE
TS100 8"	8	210	TOP HUNG	1200	300	10	13/14 & 16/17	62
TS100 10"	10	260	TOP HUNG	1200	450	16	13/14 & 16/17	56
TS100 12"	12	311	TOP HUNG	1200	600	21	13/14 & 16/17	64
TS100 16"	16	406	TOP HUNG	1200	750	22	13/14 & 16/17	51
TS100 16"	16	406	SIDE HUNG	700	1300	26	13/14 & 16/17	51
TS100 20"	20	511	TOP HUNG	1200	900	24	13/14 & 16/17	42
TS100 24"	24.3	616.5	TOP HUNG	1200	1200	32	13/14 & 16/17	38
TS201	12	311	TOP/SIDE HUNG	650	1250	20	13/14 & 16/17	60
TS216	16	406	TOP/SIDE HUNG	700	1300	24	13/14 & 16/17	52

IT IS THE RESPONSIBILITY OF THE WINDOW MANUFACTURER TO ENSURE THAT THE FINISHED WINDOW MEET ANY REQUIRED SAFETY AND PERFORMANCE SPECIFICATIONS